

Printing date 12/16/2005

Reviewed on 12/16/2005

**1 Identification of substance**· Product details

- Trade name: **Concrete Film Remover**
- Article number: 10810, 10811
- Application of the substance / the preparation Cleaning agent/ Cleaner
- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH      Tel. +49(0)911-642960  
Lechstrasse 28      Fax. +49(0)911-644456  
D 90451 Nürnberg      e-mail info@akemi.de
- Information department: Laboratory

**2 Composition/Data on components**· Chemical characterization

- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 7664-38-2	phosphoric acid	12.5-25%
EINECS: 231-633-2	C; R 34	
EU Number: 015-011-00-6		
CAS: 7647-01-0	hydrogen chloride	12.5-25%
EINECS: 231-595-7	C; R 34-37	
EU Number: 017-002-01-X		
	Aliphatic alcohols, C13-C15, largely linear, ethoxylated	1-5%
	Xn, N; R 22-41-50	
CAS: 110-65-6	but-2-yne-1,4-diol	<1%
EINECS: 203-788-6	T; R 21-23/25-34-43-48/22	
EU Number: 603-076-00-9		

- Additional information: For the wording of the listed risk phrases refer to section 16.

**3 Hazards identification**

- Hazard description: C Corrosive
- Information pertaining to particular dangers for man and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
Causes burns.  
Irritating to respiratory system.
- Classification system: The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4) Health = 3  
Fire = 0  
Reactivity = 0
- HMIS-ratings (scale 0 - 4) Health = 3  
Fire = 0  
Reactivity = 0

**4 First aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 2)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/16/2005

Reviewed on 12/16/2005

Trade name: **Concrete Film Remover**

(Contd. of page 1)

**5 Fire fighting measures**

- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards caused by the material, its products of combustion or resulting gases: Hydrogen chloride (HCl)
- Protective equipment: Wear self-contained respiratory protective device.  
Wear fully protective suit.

**6 Accidental release measures**

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.  
Particular danger of slipping on leaked/spilled product.
- Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

**7 Handling and storage**

- Handling:
- Information for safe handling: Keep receptacles tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Protect from heat and direct sunlight.  
Keep receptacle tightly sealed.  
Protect from frost.

**\* 8 Exposure controls and personal protection**

- Additional information about design of technical systems: No further data; see item 7.
  - Components with limit values that require monitoring at the workplace:
- 
- 7664-38-2 phosphoric acid**
- PEL 1 mg/m<sup>3</sup>  
REL Short-term value: 3 mg/m<sup>3</sup>  
Long-term value: 1 mg/m<sup>3</sup>  
TLV Short-term value: 3 mg/m<sup>3</sup>  
Long-term value: 1 mg/m<sup>3</sup>
- Additional information: The lists that were valid during the creation were used as basis.
  - Personal protective equipment:
  - General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

(Contd. on page 3)

USA

# Material Safety Data Sheet

## acc. to ISO/DIS 11014

Printing date 12/16/2005

Reviewed on 12/16/2005

Trade name: **Concrete Film Remover**

(Contd. of page 2)

- Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands: Protective gloves
- Material of gloves Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
Nitrile rubber, NBR  
Chloroprene rubber, CR  
PVC gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles
- Body protection: Protective work clothing

### 9 Physical and chemical properties

#### · General Information

Form: Fluid  
Color: Yellow-brown  
Odor: Pungent

#### · Change in condition

Melting point/Melting range: Undetermined.  
Boiling point/Boiling range: Undetermined.

#### · Flash point:

Not applicable.

#### · Auto igniting:

Product is not selfigniting.

#### · Danger of explosion:

Product does not present an explosion hazard.

#### · Vapor pressure at 20°C (68°F):

20.0 hPa (15 mm Hg)

#### · Density at 20°C (68°F):

1.150 g/cm<sup>3</sup>

#### · Solubility in / Miscibility with Water:

Fully miscible.

#### · pH-value at 20°C (68°F):

&lt; 1

### 10 Stability and reactivity

#### · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

#### · Dangerous reactions

Reacts with strong oxidizing agents.  
Reacts with metals forming hydrogen.

#### · Dangerous products of decomposition:

Hydrogen chloride (HCl)

### 11 Toxicological information

#### · Acute toxicity:

#### · Primary irritant effect:

##### · on the skin:

Caustic effect on skin and mucous membranes.

##### · on the eye:

Strong caustic effect.

#### · Sensitization:

No sensitizing effects known.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive  
Irritant

(Contd. on page 4)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/16/2005

Reviewed on 12/16/2005

Trade name: **Concrete Film Remover**

(Contd. of page 3)

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

## 12 Ecological information

- General notes: Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Water hazard class 2 (Self-assessment): hazardous for water. Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

## 13 Disposal considerations

- Product:
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations. Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

## 14 Transport information

- DOT regulations:
- Hazard class: 8
- Identification number: UN3264
- Packing group: II
- Proper shipping name (technical name): CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)
- Label 8
- Land transport ADR/RID (cross-border):
- ADR/RID class: 8 (C1) Corrosive substances
- Danger code (Kemler): 80
- UN-Number: 3264
- Packaging group: II
- Description of goods: 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)
- Maritime transport IMDG:
- IMDG Class: 8
- UN Number: 3264
- Label 8
- Packaging group: II
- EMS Number: F-A,S-B
- Marine pollutant: No
- Propper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 8
- UN/ID Number: 3264
- Label 8
- Packaging group: II
- Propper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)

(Contd. on page 5)

USA



**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 12/16/2005

Reviewed on 12/16/2005

Trade name: **Concrete Film Remover**

(Contd. of page 5)

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS: Laboratory
- Contact: Dieter Zimmermann
- \* Data compared to the previous version altered.

USA