

Printing date 11/17/2005

Reviewed on 11/17/2005

* 1 Identification of substance

· Product details

- Trade name: **Stain Repellent**
- Article number: 10849, 10850, 10851
- Application of the substance / the preparation Protective impregnation
- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-642960
Lechstrasse 28 Fax. +49(0)911-644456
D 90451 Nürnberg e-mail info@akemi.de
- Information department: Laboratory

* 2 Composition/Data on components

· Chemical characterization

- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	50-100%
EINECS: 265-150-3	Xn; R 10-65-66	
EU Number: 649-327-00-6		
EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy	1-5%
EU Number: 649-330-00-2	Xn; R 10-65	
CAS: 64741-65-7	Naphtha (petroleum), heavy alkylate	1-5%
EINECS: 265-067-2	Xn; R 53-65-66	
EU Number: 649-275-00-4		

- Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description: Xn Harmful
- Information pertaining to particular dangers for man and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Flammable.
Harmful: may cause lung damage if swallowed.
Repeated exposure may cause skin dryness or cracking
- Classification system: The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4) Health = 2
Fire = 2
Reactivity = 0
- HMIS-ratings (scale 0 - 4) Health = 2
Fire = 2
Reactivity = 0

4 First aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/17/2005

Reviewed on 11/17/2005

Trade name: **Stain Repellent**

(Contd. of page 1)

5 Fire fighting measures

- Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards caused by the material, its products of combustion or resulting gases: Formation of toxic gases is possible during heating or in case of fire.
- Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- Handling:
- Information for safe handling: Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Components with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Immediately remove all soiled and contaminated clothing.
Avoid contact with the eyes and skin.
- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
Filter AX
- Protection of hands: Protective gloves
- Material of gloves: Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/17/2005

Reviewed on 11/17/2005

Trade name: **Stain Repellent**

(Contd. of page 2)

- Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles
- Body protection: Protective work clothing

* 9 Physical and chemical properties

· General Information

Form: Fluid
Color: Colorless
Odor: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: > 150°C (> 302°F)

· Flash point: > 40°C (> 104°F)

· Ignition temperature: 240°C (464°F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 0.6 Vol %
Upper: 7.0 Vol %

· Vapor pressure at 20°C (68°F): 1.1 hPa (1 mm Hg)

· Density at 20°C (68°F): ~ 0.76 g/cm³

· Solubility in / Miscibility with Water:

Not miscible or difficult to mix.

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Dangerous reactions

Reacts with strong oxidizing agents.
 Forms flammable gases / fumes.

· Dangerous products of decomposition:

Carbon monoxide and carbon dioxide

* 11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >3000 mg/kg (rab)

· Primary irritant effect:

· on the skin:

No irritant effect.

· on the eye:

No irritating effect.

· Sensitization:

No sensitizing effects known.

· Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations:

* 12 Ecological information

· General notes:

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/17/2005

Reviewed on 11/17/2005

Trade name: **Stain Repellent**

(Contd. of page 3)

Water hazard class 1 (Self-assessment): slightly hazardous for water

13 Disposal considerations

- Product:
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations. Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport information

- DOT regulations:
- Hazard class: 3
- Identification number: NA1993
- Packing group: III
- Proper shipping name (technical name): COMBUSTIBLE LIQUID, N.O.S (DIESEL FUEL)
- Label: 3
- Land transport ADR/RID (cross-border):
- ADR/RID class: 3 (F1) Flammable liquids
- Danger code (Kemler): 30
- UN-Number: 1993
- Packaging group: III
- Description of goods: 1993 FLAMMABLE LIQUID, N.O.S., special provision 640E (DIESEL FUEL)
- Maritime transport IMDG:
- IMDG Class: 3
- UN Number: 1993
- Label: 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (DIESEL FUEL)
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 1993
- Label: 3
- Packaging group: III
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (DIESEL FUEL)

15 Regulations

- Sara
- Section 355 (extremely hazardous substances):
None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
64742-48-9 Naphtha (petroleum), hydrotreated heavy
Naphtha (petroleum), hydrodesulfurized heavy
64741-65-7 Naphtha (petroleum), heavy alkylate
- Proposition 65
- Chemicals known to cause cancer:
None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity:
None of the ingredients is listed.

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/17/2005

Reviewed on 11/17/2005

Trade name: **Stain Repellent**

(Contd. of page 4)

- Carcinogenicity categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

- NTP (National Toxicology Program)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

- MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- Product related hazard

- informations:

The product has been classified and marked in accordance with directives on hazardous materials.

- Hazard symbols:

Xn Harmful

- Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

- Risk phrases:

Flammable.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking

- Safety phrases:

Keep out of the reach of children.

Do not breathe fumes

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point

Wear suitable gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

- National regulations:

- Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS:

Laboratory

- Contact:

Dieter Zimmermann

- * Data compared to the previous version altered.