

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME(S) **HERTRON INT'L REGENT STONE SOAP(AEROSOL)**
APOLLO PRODUCT NO.: **4971**
Manufactured By: **APOLLO INDUSTRIES, INC.**
1850 S. Cobb Industrial Blvd.
Smyrna, GA 30082
(770)433-0210(8am-5pm; M-F)
(800)255-3924(24 Hr Emergency)

PREPARATION DATE **October 14, 2003**
PREPARED BY **Vena Burnell**

2. COMPOSITION/INFORMATION ON INGREDIENTS

OSHA HAZARDOUS INGREDIENTS TABLE

<u>CHEMICAL</u>	<u>CAS #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Liquefied Petroleum Gas	68476-86-8	Unknown	1000 ppm

* Indicates ingredients which are subject to the reporting requirements of Section 313 of EPCRA and 40 CFR 372

3. HAZARDS IDENTIFICATION

HMS RATING: Health 0, Flammability 1, Reactivity 0
NFPA RATING: Toxicity 0, Flammability 1, Reactivity 2

HEALTH EFFECTS

Inhalation	Unknown
Eye Contact	May cause slight irritation. May cause stinging and tearing.
Skin Contact	May cause slight irritation.
Ingestion	Unknown

PRIMARY ROUTES OF EXPOSURE: skin

CONDITIONS AGGRAVATED BY EXPOSURE: None known.

ANY INGRED. LISTED CARCINOGEN: OSHA Not listed. IARC Not listed. NTP Not listed.

4. FIRST AID

Inhalation	Immediately remove victim to fresh air. If victim has stopped breathing give artificial respiration, preferably by mouth-to-mouth. Get medical attention immediately.
Eye Contact	Immediately flush eyes with plenty of cool water for at least 15 minutes. Do not let victim rub eyes. Get medical attention immediately.
Skin Contact	Wash affected area.
Ingestion	Call a physician or poison control center promptly.

5. FIRE FIGHTING MEASURES

Extinguisher Media	Foam, Dry Chemical (B-C), CO ₂ , Water Spray
Flammability per Flame Projection Test	Non-Flammable

SPECIAL FIRE FIGHTING PROCEDURES: Keep containers cool using water spray to avoid bursting.

UNUSUAL HAZARDS: Contents under pressure. Do not use near fire, sparks, or flame. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause container to burst.

6. ACCIDENTAL RELEASE MEASURES

PROCEDURES FOR CLEANING UP LEAKS AND SPILLS: Absorb spill with inert material then place in a chemical waste container. Dispose of spill material in accordance with regulatory requirements.